



Pheilix Luxury Version

380V 16/32A 11kW/22kW Commercial use , Ocpp2.0 protocol , App monitoring

	Basic Specification	Key Features	Packing Details
 <p>Product Code No : EVCTP1116SRF/2232SRF(Socket) EVCTP1116TRF/2232TRF(tethered)</p>	<ul style="list-style-type: none"> • Housing case : Metal • Input/Out put : 380V 16/32A • Grid Condition : TT/TNCS • Rated Power : 11/22kW • Charge Interface : Type 2 • IP/IK : IP65/IK10 • Work Tem : -30~ 55°C • Power consumption: 5w • Humidity : 5%-95% • Attitude : >2000m • Earth leakage : Type A+6mA • Over/Under Voltage : Yes • Over Current : Yes • Over Tem : Yes • Ground Test : Yes 	<ul style="list-style-type: none"> • Ocpp2.0 protocol (Pheilix platform) • App Smart charging(Pheilix smart App) • *3 RFIDs Cards for On/Off line use • Wifi+Ethernet(RJ45)+Blue tooth (4G is optional) • PEN fault & No earth rod required(for UK) • Independent MID Meter + AC Contactors • Commercial operating function • Off-peak /Randomized delay/Anti-tamper(UK) • Dynamic load balance (Optional) • Solar & Battery compatibility(Optional) • Zero Emission system compatibility (Optional) • Ocpp Management office Service(Optional) • App Management office Service(Optional) 	<ul style="list-style-type: none"> • Package size : 52*35*22cm • Pallet size : 120x100x20cm • Qtys/Pallet : 40 units • Weight : 10Kg / Ea • 40HQ Qtys : 1200 units • Delivery time : 60 days • Certification : TUV/BV/CE/CB/UKCA • Warranty : 3 years <p>Powered by  Pheilix smart</p>

Note : *1, More customized configuration is available .