

3.5KW / 7KW / 11KW Portable EV Charger

Secure and Safe

Type A+30mA leakage protection

Over temperature protection

High protection grade up to Ip65


Friendly Interface

OLED Display


Current can 8A, 10A, 13A, 16A, 20A, 32A, adjustable

High compatibility

Fully compatible with all ev in the market



SAE J1772 Type 1



IEC62196-2 (Type 2)



Schuko Plug



NEMA6-20P Plug



NEMA Plug



Blue CEE



Model	SEC035K-P035	SEC7K-P7	SEC11K-P11
-------	--------------	----------	------------

Technical features

Charging capacity	Up to 3.5KW	Up to 7KW	Up to 11KW
Input/Output power	230VAC±20%,50/60Hz 8A-10A-13A-16A adjustable,1-phase	230VAC±20%,50/60Hz, 8A-16A-20A-32A adjustable,1-phase	400VAC±10%, 50/60Hz, 8A-10A-13A-16A adjustable, 3-phase
RCD	Type AC 30mA/ RCMU(Type A+DC6mA)(Optional)		
Standby power	<2W		
Measuring accuracy	1%		
User interface	LED , OLED , Select button		
Certificate/Compliance	CE/IEC61851-1,IEC61851-22,SAEJ1772		
Charging Interface	5M cable, Type2 Plug		
Power Cord Plug	Schuko/NEMA 6-20P	NEMA 14-50/Blue CEE	Blue CEE

Physical properties

Protection	IP65,IK10		
Special Protection	Temperature sensor and plug adapter		
Cooling	Natural cooling		
Operating temperature	-30C°to+55C°		
Humidity	Max.95%(non-regulating)		
Product Dimensions	210*88*50(L*W*H)mm		
Package Dimension	350*320*60(L*W*H)mm		
Net Weight	2.02Kg	2.5Kg	
Gross Weight	2.25Kg	2.7Kg	